## **MATERIAL SAFETY DATA SHEET**

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFAC	CTU	RER'S INFORMATION	N			
FPA Rating: Health-1; Flammability-1; Reactivity-0; Special-0  HMIS Rating: Health-1; Flammability-1; Reactivity-0; Personal Protection-B						
	DOT Hazard Classification: ORM-D					
	Identity (trade name as used on label):					
Marietta, GA 30062	MISTY WATER BASED CHALKBOARD CLEANER					
Date Prepared: 06/15/94 Prepared By: ES	MSI	OS Number: 101	Revi	sion- 14		
formation Calls: (770)422-2071  MERGENCY RESPONSE NUMBER: 1(800)255-3924  NOTICE: JUDGMENT BASED ON INDIRECT TEST DATA						
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION						
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES CAS Number SARA OSHA PEL ACGIH Carcinogen						
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		071011111111111111111111111111111111111	III LIST	(ppm)	TLV (ppm)	Ref. Source **
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d
		74-98-6	No	1000	1000	d
AMMONIUM HYDROXIDE		1336-21-6	No	35	25	d
ISOPROPANOL		67-63-0	No	500	400	d
SECTION 2 - PHYSICAL/CHE	=MIC	CAL CHARACTERIS	TICS			
Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = 0.980						
	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
	Evaporation Rate ( = 1): N/E					
	Water Reactive: No					
Appearance and Odor: White foam, mint fragrance and alcohol odor.						
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA						
FLAMMABILITY as per USA FLAME PROJECTION TEST  Auto Ignition Temperature  Flammability Limits in Air by % in Volume:						
(aerosols) NON-FLAMMABLE N/E % LEL: N/E % UEL: N/E						
FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.  EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide,water.						
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.						
SECTION 4 - REACTIVITY HAZARD DATA						
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR						
Incompatibility (Mat. to avoid): Strong oxidizers Conditions to Avoid: Open flame, welding arcs, heat.						
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide.						
SECTION 5 - HEALTH HAZARD DATA						
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS						
ACUTE EFFECTS						
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.						
Eye Contact: Slight irritation. Skin Contact: Slight irritation.						
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.						
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Headache, dizziness, nausea, possible unconsciousness if vapor						
conc. exceeds TLV. Lab animals have experienced anemia, liver, lung, blood damage to Glycol Ether EB.						
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.						
EMERGENCY FIRST AID PROCEDURES						
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.						
Skin Contact: Wash with soap and water. If irritated, seek medical attention.						
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.						
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.						
SECTION 6 - CONTROL AND PROTECTIVE MEASURES						
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH to be used in positive pressure mode.						
Protective Gloves: Disposable latex gloves suggested.  Eye Protection: Safety glasses recommended.						
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.						
Other Protective Clothing & Equipment: None						
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.						
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE						
Steps To Be Taken If Material Is Spilled Or Released: Flush to sewer with water.						
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.						
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.						
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.						

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only