MATERIAL SAFETY DATA SHEET This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

This MSDS complies with OSHA'S Hazard Comr					7 -		
IDENTITY AND MANUFACTURER'S INFORMATION							
FPA Rating: Health-2; Flammability-0; Reactivity-0; Special-0 HMIS Rating: Health-2; Flammability-0; Reactivity-0; Personal Protection-							
Manufacturer's Name: AMREP, INC.	-	DOT Hazard Classification: ORM-D					
Address: 990 Industrial Park Drive	Ide	ntity (trade name as us		,			
Marietta, GA 30062		MISTY PENETRATING LUBRICANT					
Date Prepared: 10/11/95 Prepared By: DL	MS	MSDS Number: 390 Revision- 17 NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA					
Information Calls: (770)422-2071 EMERGENCY RESPONSE NUMBER: 1(800)255-3924					DIRECT TE	ST DATA	
SECTION 1 - MATERIAL	IDENTIFI		MATION		-	-	
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES		CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)			III LIST	(ppm)	TLV (ppm)	Ref. Source **	
TRICHLOROETHYLENE		79-01-6	Yes	50	50	b	
		127-18-4	Yes	25	25	a,b	
PETROLEUM DISTILLATE		64742-54-7	Yes	5mg\M3	5mg\M3	d	
BARIUM PETROLEUM SULFONATE		61760-48-5	Yes	5mg\M3	5mg\M3	d	
WARNING: This product contains a chemical or chemicals kn the State of California to cause cancer.	own to						
SECTION 2 - PHYSICA Boiling Point: N/A				rato Ophy - 1	11		
Vapor Pressure: PSIG @ 70°F (Aerosols): 85-100 Vapor Density (Air = 1): N/E	por Pressure (Non-Aerosols)(mm Hg and Temperature): N/A aporation Rate (n-butyl acetate= 1): 2.1 (concentrate only)						
Solubility in Water: Insoluble		ter Reactive: No	aceiale=	T). 2.1 (CONC	entrate only)		
Appearance and Odor: Light brown odor with chlorinated solvent odor.	Wa						
SECTION 3 - FIRE A		OSION HAZARD DA	тΔ				
FLAMMABILITY as per USA FLAME PROJECTION TEST		inition Temperature		ability Limite	in Air by % i	n Volume:	
(aerosols) NON-FLAMMABLE	Auto iç	Ito Ignition Temperature Flammability Limits in Air by % in Volume: N/E % LEL: N/E % UEL: N/E					
FLASH POINT AND METHOD USED (non-aerosols): N/A							
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing appa		INGUISHER MEDIA.	Uarri, ury	chemical, car	on aloxide.		
Unusual Fire & Explosion Hazards: Do not expose aerosols to tempera		e 130°F or the container	may rupti	ire			
		Y HAZARD DATA	ind) idpl				
STABILITY [X] STABLE [] UNSTABLE		ZARDOUS POLYMERIZ] WILL []	X] WILL NOT	OCCUR	
Incompatibility (Mat. to avoid): Reactive metals, aluminum, magnesium, soxidizing agents.						000011	
Hazardous Decomposition Products: CO2, CO, HCI, small amounts of	phosgene	and chlorine.					
SECTION 5 -	HEALTH	HAZARD DATA					
PRIMARY ROUTES OF ENTRY: [X] INHALATION []	NGESTION	I [X] SKIN ABSORP	FION []	EYE []NO	OT HAZARDO	US	
ACUTE EFFECTS:							
Inhalation: Excessive inhalation of vapors can be harmful and may cause	headache,	dizziness, asphyxia, an	esthetic ef	fects and poss	sible unconsci	ousness.	
Eye Contact: Irritation Skin Contact: Irritation due to defatting of skin.							
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea				ng er eran			
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw mater		nixture) Mav cause live	r abnorma	lities, kidnev	spleen. luna o	brain damage	
cardiac abnormalities. Perchloroethylene has been shown to increase the							
Medical Conditions Generally Aggravated by Exposure: May aggrava							
		D PROCEDURES					
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical at							
Skin Contact: Wash with soap and water. If irritated, seek medical attent							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attent							
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of wa		mediate medical attactiv	n				
SECTION 6 - CONTROL							
Respiratory Protection (specify type): If vapor concentration exceeds T	LV, use re	spirator approved by U.S	6. Bureau	of Mines for or	ganic vapor.		
Protective Gloves: Neoprene gloves recommended.		Protection: Safety gla	isses reco	mmended.			
Ventilation Requirements: Adequate ventilation to keep vapor concentra	ation below	TLV.					
Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling for							
SECTION 7 - PRECAUTIO							
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suita to evaporate if small spill. DO NOT FLUSH TO SEWER.	able mediu	m. Incinerate or landfill	according	to local, state	or Federal reg	ulations. Allow	
Waste Disposal Methods: Aerosol cans when vented to atmospheric pre	ssure throu	gh normal use, pose no	disposal h	nazard.			
Precautions To Be Taken In Handling & Storage: Do not puncture or in		a			80°F.		
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF C							
We believe the statements, technical information and recommendations co						tee of anv kind	
** Chemical Listed as Carcinogen or Potential Carcinogen. [ARC Monograph [c] OS	-				

THIS MSDS IS CURRENT AS OF JANUARY 10, 2000. The DATE PREPARED section is the original date assembled and remains current until a change is necessary. This is tracked internally at the manufacturer by these date codes and therefore must remain as the originating date.