## MATERIAL SAFETY DATA SHEET

TI I MODO

	This MSDS complies with OSHA'S Hazard				and USHA F	01111174			
			BUTOR'S INFORMAT						
NFPA Rating: Health-2;			S Rating: Health-2; F			ty-0; Persona	al Protection-B		
Manufactured For:	Lagasse, Inc.	-	DOT Hazard Classification: ORM-D						
Address:	One Parkway North	Idei	Identity (trade name as used on label):						
	Deerfield, IL 60015		BOARDWALK DUST MAGNET DUST MOP TREATMENT						
Phone:	Phone: 800-989-7847 M				MSDS Number: A06412 Revision- 11				
			Date Prepared: 01/15/07 Prepared by: IB						
	oonse Number: Chemtel: 800-255-3924	mation Calls: (770)422		1 1	epareu by. I	D			
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA Information Calls: (770)422-2071 SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION									
COMPONENTS-CHEMIC	CAL NAMES AND COMMON NAMES		CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen		
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)				III LIST	(ppm)	TLV (ppm)	Ref. Source **		
PETROLEUM DISTILLATE			8052-41-3	No	500	100	d		
PETROLEUM DISTILLATE			64742-54-7 /	No	5mg/M3	5mg/M3	d		
			64742-53-6						
ISOBUTANE / PROPANE BLEND			75-28-5	No	800	800	d		
			74-98-6	No	1000	1000	d		
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS           Boiling Point: N/A         Specific Gravity (H2O=1): Concentrate Only = 0.93									
	@ 70°F (Aerosols): Max. 50						1		
Vapor Density (Air = 1):		Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A Evaporation Rate ( = 1): N/E							
Solubility in Water: Emulsifiable Water Reactive: No									
Appearance and Odor: White, creamy spray with pine fragrance.									
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA									
FLAMMABILITY as pe	r USA FLAME PROJECTION TEST	Auto Ig	nition Temperature	Flamm	nability Limit	s in Air by %	in Volume:		
(aerosols): less than 1			N/E		.: N/É	% ÚEL			
	EGORIZED AS FLAMMABLE								
FLASH POINT AND METHOD USED (non-aerosols): N/A EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water.									
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.									
SECTION 4 - REACTIVITY HAZARD DATA									
STABILITY     [X]     STABLE     HAZARDOUS POLYMERIZATION     []     WILL     [X]     [X] <th[x]< th="">     [X]     [X]     [X]     &lt;</th[x]<>									
Incompatibility (Mat. to avoid): Strong oxidizers. Conditions to Avoid: Open flame, welding arcs, heat, sparks.									
Hazardous Decomposition Products: CO, CO2.									
SECTION 5 - HEALTH HAZARD DATA									
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS									
ACUTE EFFECTS:									
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.									
Eye Contact: Irritation Skin Contact: Irritation									
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.									
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Dermatitis.									
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.									
EMERGENCY FIRST AID PROCEDURES									
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.									
Skin Contact: Wash with soap and water. If irritated, seek medical attention.									
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.									
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.									
SECTION 6 - CONTROL AND PROTECTIVE MEASURES									
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH for organic vapor.									
Protective Gloves: Disposable Latex or Nitrile. Eye Protection: Safety glasses.									
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.									
Other Protective Clothing & Equipment: Eyewash station recommended.									
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing. SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE									
SECTION 7 - PRECADITIONS FOR SAFE HANDLING AND USE Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal									
regulations. DO NOT FLUSH TO SEWER.									
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.									
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.									
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Remove ignition sources. Avoid									
prolonged breathing of spray mist.									
We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.									
** 01				1 0 0 1 1 4 5		1 4 1 1 0 1	0.1		

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only THIS MSDS IS CURRENT AS OF November 2, 2010. The DATE PREPARED section is the original date assembled and remains current until a change is necessary. This is tracked internally at the manufacturer by these date codes and therefore must remain as the originating date.