National Fire Protection
Association (NFPA)

Fire Hazard
Health

Reactivity

Health

Health

Reactivity

Health

Reactivity

Health

Reactivity

Health

Reactivity

Health

Reactivity

Health

Reactivity

Reactivity

Health

Reactivity

Reactivity

Specific Hazard

Protective Clothing



Emergency Tan. Aerosol. See Section 9. **Overview** DANGER. CORROSIVE. CA

DANGER. CORROSIVE. CAUSES EYE AND SKIN BURNS. HARMFUL OR FATAL IF SWALLOWED. CONTENTS

UNDER PRESSURE.

Section 1. Chemical Product and Company Identification			
Product Name	MR. MUSCLE OVEN AND GRILL CLEANER - AEROSOL	Code	91206
Product Use	Industrial/Institutional: Cleaning product.	PMS#	433200
MSDS#	126040003	Validation Date	3/7/2002
U.S. Headquarters		Print Date	3/7/2002
Drackett Professional		Supersedes	3/7/2002.
A Division of S.C. Johnson Commercial Markets, Inc. 8310 16th Street Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249		In Case of Emergency	(800) 851-7145

Section 2. Composition and Information on Ingredients				
Ingredients	CAS#	% by Weight	Exposure Limits	LC50/LD50
Monoethanolamine	141-43-5	1-5	OSHA (United States). TWA: 8 mg/m³ STEL: 15 mg/m³ ACGIH (United States). TWA: 7.5 mg/m³ STEL: 15 mg/m³	ORAL (LD50): Acute: 1720 mg/kg [Rat]. DERMAL (LD50): Acute: 1018 mg/kg [Rabbit].
Butane	106-97-8	1-5	OSHA (United States). TWA: 1900 mg/m³ ACGIH (United States). TWA: 1900 mg/m³	Not available.
Isobutane	75-28-5	1-5	Not available.	VAPOR (LC50): Acute: 0.0057 ppm 0.25 hour(s) [Rat].
Sodium Hydroxide	1310-73-2	1-5	OSHA (United States). CEIL: 2 mg/m³ ACGIH (United States). STEL: 2 mg/m³	Not available.
Diethylene Glycol Butyl Ether	112-34-5	10-30	Not available.	ORAL (LD50): Acute: 5660 mg/kg [Rat]. DERMAL (LD50): Acute: 2700 mg/kg [Rabbit].
Water	7732-18-5	60-100	Not available.	Not available.

Section 3. Hazards Identification	
Routes of Entry	Inhalation. Skin contact. Eye contact.
Potential Acute Health El	ffects
	Eyes Corrosive. May cause permanent damage including blindness.
	Skin Corrosive. May cause permanent damage.
Inha	May cause irritation and corrosive effects to nose, throat and respiratory tract.
Ingo	estion Corrosive. May cause burns to mouth, throat, and stomach.

Medical Conditions Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may Aggravated by Overexposure: be more susceptible to irritating effects.

See Toxicological Information (section 11)

Section 4. First Aid Measures	
Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.
Skin Contact	Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures		
Flammability of the Product Flash Points	NFPA 30B Level 1 Aerosol. CLOSED CUP: <-7°C (19.4°F).	
Products of Combustion	None known.	
Fire Fighting Media and Instructions	Use water spray to keep fire-exposed containers cool. Dry chemical, carbon dioxide. Fight fire from protected location or maximum possible distance. In case of fire and/or explosion do not breathe fumes.	
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8).	
Special Remarks on Fire and Explosion Hazards	Aerosol product - Containers may rocket or explode in heat of fire. Corrosive material (See sections 8 and 10).	

Section 6. Accidental Release Measures		
Personal Precautions	Put on appropriate personal protective equipment (see Section 8).	
Environmental Precautions and Clean-up Methods	Eliminate all ignition sources. In the event of major spillage: Use appropriate containment to avoid environmental contamination. Take up with sand or other non-combustible material. Place in suitable clean, dry containers for disposal by approved methods.	

Section 7. Handling and Storage		
Handling	Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Use only in well-ventilated areas. Do not puncture or incinerate. FOR INDUSTRIAL USE ONLY.	
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep container tightly closed. Keep away from heat, sparks and flame. Pressurized container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. KEEP OUT OF REACH OF CHILDREN.	

Section 8. Exposure Controls/Personal Protection		
Engineering Controls	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.	
Personal Protection		
Eyes	Chemical splash goggles.	
Hands	Chemical resistant gloves. Includes: Neoprene gloves. Rubber gloves.	
Respiratory	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.	
Feet	Protective footwear.	
Body	If major exposure is possible, wear suitable protective clothing and footwear.	

Section 9. Physical and Chemical Properties

Physical State and

Appearance

Liquid. (Aerosol.)

Odor Citrus.

Color Tan.
pH 13 [Basic.]

Specific Gravity 1

Boiling/Condensation Point100°C (212°F)Melting/Freezing Point0°C (32°F)Viscosity300 cP (Dynamic).

Solubility in water Complete.

Section 10. Stability and Reactivity

Stability and Reactivity
Conditions of Instability
The product is stable.
Excessive heat.

Incompatibility with Various Substances

Reactive with acids.

Hazardous Decomposition

Products

When exposed to fire: Produces normal products of combustion. Toxic decomposition products include:

Oxides of sodium.

Hazardous Polymerization Will not occur.

Section 11. Toxicological Information

Acute toxicity Corrosive.

Effects of Chronic Exposure None known.

Other Toxic Effects

Contains approximately 0.1% Cristobalite (CAS# 14464-46-1), NJ, PA, MA, NTP. This formulation is a heavy, viscous liquid. Therefore, respirable-size particles of dry Cristobalite are not expected to become

airborne and will not be inhaled.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information Undiluted product is regulated under environmental and transportation laws as a corrosive waste. If

possible, recycle empty aerosol cans to the nearest steel recycling center. Use up package or give to

someone who can. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification

DOT Proper Please refer to the Bill of Lading/receiving documents for up to date shipping information. **Shipping Name**

TDG Classification

TDG Proper Shipping Name TDG Class Please refer to the Bill of Lading/receiving documents for up to date shipping information.

Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2

US Regulations

Federal Clean Water Act (CWA) 311: Sodium hydroxide

Clean air act (CAA) 112 accidental release prevention: Butane

Clean air act (CAA) 112 regulated flammable substances: Butane, Isobutane

CERCLA: Hazardous substances.: Diethylene Glycol Butyl Ether, Isobutane, Sodium hydroxide

State New Jersey spill list: Diethylene Glycol Butyl Ether, Sodium hydroxide

New Jersey: Monoethanolamine, Diethylene Glycol Butyl Ether, Butane, Isobutane, Sodium hydroxide

Massachusetts spill list: Monoethanolamine, Butane, Isobutane, Sodium hydroxide Massachusetts RTK: Monoethanolamine, Butane, Isobutane, Sodium hydroxide

Pennsylvania RTK: Monoethanolamine, Diethylene Glycol Butyl Ether, Butane, Isobutane, Sodium

hydroxide

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Not applicable.

Information

Canadian Regulations

WHMIS Classification CLASS A: Compressed gas.

CLASS E: Corrosive liquid.

WHMIS Icon



Registered Product Not applicable. Information

Chemical Inventory Status

All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16. Other Information

Other Special

MSDS Serial Range: 001-003

Considerations

Version 1.01

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.