N/A= Not Applicable Effective Date: 1/09 Revision: n/a

SECTION 1-PRODUCT IDENTIFICATION AND SUPPLIER INFORMATION

 Product Name: Extra Point
 Manufactured For: Triple S

 Generic Name: Stainless Steel Polish
 Address: 2 Executive Park Drive
 Billerica, MA 01862

 Chemical Family: Mineral Oil Blend
 Address: 2 Executive Park Drive
 Billerica, MA 01862

 Formula: Proprietary Triple S Product Number: 48123
 Phone #: 800-323-2251
 Billerica, MA 01862

 CHEMICAL NAME
 CAS NO.
 WT. %
 PEL
 TWA-TLV
 STEL-TLV

CHEMICAL NAME	CAS NO.	WT. %	PEL	TWA-TLV	STEL-TLV
Petroleum Distillate	64742-88-7	20 to 30	500 ppm	100 ppm	N/A
Mineral Seal Oil	64742-55-8	20 to 30	N/A	N/A	N/A
White Mineral Oil	8042-47-5	40 to 60	N/A	N/A	N/A

SECTION 3-PHYSICAL DATA	SECTION 4-FIRE AND EXPLOSION HAZARD DATA				
Boiling Point (°F): 316 F. Initial Specific Gravity: 0.828	Flash Point (Method Used): 127° F. (TCC)				
Vapor Pressure: <10mm Hg @ 68 F. Vapor Density (Air=1): >1	Upper Explosion Limit: N/A Lower Explosion Limit: N/A				
% Volatile: < 30% pH: N/A	Extinguishing Media: Foam, CO ₂ , Dry Chemical				
Solubility in Water: Nil Evaporation Rate (Water=1): <1	Special Firefighting Procedures: Do Not Use Water.				
Physical Description: Slightly viscous clear liquid with solvent odor.	Unusual Fire and Explosion Hazards: Drums heated by fire can explode.				
SECTION 5-REACTIVITY DATA					
Stability: Stable	Hazardous Polymerization: None				
Hazards Decomposition Products: Carbon monoxide possible if burned. Incompatibility (Materials to Avoid): Strong oxidizers.					
SECTION 6-STORAGE AND	HANDLING INFORMATION				
Combustible liquid - Avoid contact with heat, spark or open flame. Use only with ad	lequate ventilation. Avoid breathing of vapors or mists. Keep out of reach of children.				
For use by trained personnel only. Keep container closed during storage. For institu	tional and industrial use only. Avoid contact with eyes, skin and clothing. Wash				
thoroughly with soap and water after handling.					
SECTION 7-HEALTH HAZARDS AND FIRST AID	SECTION 8-SPECIAL PROTECTION INFORMATION				
SECTION 7-HEALTH HAZARDS AND FIRST AID Effects of Overexposure:					
	SECTION 8-SPECIAL PROTECTION INFORMATION Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHA approved hydrocarbon canister or respirator when using in poorly ventilated areas.				
Effects of Overexposure:	Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHA				
Effects of Overexposure: Skin: Prolonged or repeated contact may cause irritation or dermatitis. Eyes: Eye irritant. May cause redness, swelling, or blurred vision. Inhalation: May cause dizziness or drowsiness.	Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHA approved hydrocarbon canister or respirator when using in poorly ventilated areas.				
Effects of Overexposure: Skin: Prolonged or repeated contact may cause irritation or dermatitis. Eyes: Eye irritant. May cause redness, swelling, or blurred vision.	Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHA approved hydrocarbon canister or respirator when using in poorly ventilated areas. Ventilation Requirements: Provide mechanical exhaust to keep TLV of Section 2 ingredients below acceptable limit. Protective Gloves: Solvent proof rubber or neoprene.				
Effects of Overexposure: Skin: Prolonged or repeated contact may cause irritation or dermatitis. Eyes: Eye irritant. May cause redness, swelling, or blurred vision. Inhalation: May cause dizziness or drowsiness.	Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHA approved hydrocarbon canister or respirator when using in poorly ventilated areas. Ventilation Requirements: Provide mechanical exhaust to keep TLV of Section 2 ingredients below acceptable limit.				
Effects of Overexposure: Skin: Prolonged or repeated contact may cause irritation or dermatitis. Eyes: Eye irritant. May cause redness, swelling, or blurred vision. Inhalation: May cause dizziness or drowsiness. Ingestion: May cause dizziness, drowsiness or narcosis. Aspiration of material into	Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHA approved hydrocarbon canister or respirator when using in poorly ventilated areas. Ventilation Requirements: Provide mechanical exhaust to keep TLV of Section 2 ingredients below acceptable limit. Protective Gloves: Solvent proof rubber or neoprene.				
Effects of Overexposure: Skin: Prolonged or repeated contact may cause irritation or dermatitis. Eyes: Eye irritant. May cause redness, swelling, or blurred vision. Inhalation: May cause dizziness or drowsiness. Ingestion: May cause dizziness, drowsiness or narcosis. Aspiration of material into	Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHA approved hydrocarbon canister or respirator when using in poorly ventilated areas. Ventilation Requirements: Provide mechanical exhaust to keep TLV of Section 2 ingredients below acceptable limit. Protective Gloves: Solvent proof rubber or neoprene. Eye Protection: Chemical splash goggles.				
Effects of Overexposure: Skin: Prolonged or repeated contact may cause irritation or dermatitis. Eyes: Eye irritant. May cause redness, swelling, or blurred vision. Inhalation: May cause dizziness or drowsiness. Ingestion: May cause dizziness, drowsiness or narcosis. Aspiration of material into	Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHAapproved hydrocarbon canister or respirator when using in poorly ventilated areas.Ventilation Requirements: Provide mechanical exhaust to keep TLV of Section 2ingredients below acceptable limit.Protective Gloves: Solvent proof rubber or neoprene.Eye Protection: Chemical splash goggles.Other Protective Equipment: Fire extinguisher should be located nearby when				
Effects of Overexposure: Skin: Prolonged or repeated contact may cause irritation or dermatitis. Eyes: Eye irritant. May cause redness, swelling, or blurred vision. Inhalation: May cause dizziness or drowsiness. Ingestion: May cause dizziness, drowsiness or narcosis. Aspiration of material into the lungs can cause pneumonitis. First Aid Procedures: Skin: Remove contaminated clothing. Wash with soap and water. Seek medical	Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHA approved hydrocarbon canister or respirator when using in poorly ventilated areas. Ventilation Requirements: Provide mechanical exhaust to keep TLV of Section 2 ingredients below acceptable limit. Protective Gloves: Solvent proof rubber or neoprene. Eye Protection: Chemical splash goggles. Other Protective Equipment: Fire extinguisher should be located nearby when using. SECTION 9-SPILL OR LEAK PROCEDURES Steps to be taken in Case Material is Released or Spilled: Floors will become				
Effects of Overexposure: Skin: Prolonged or repeated contact may cause irritation or dermatitis. Eyes: Eye irritant. May cause redness, swelling, or blurred vision. Inhalation: May cause dizziness or drowsiness. Ingestion: May cause dizziness, drowsiness or narcosis. Aspiration of material into the lungs can cause pneumonitis. First Aid Procedures: Skin: Remove contaminated clothing. Wash with soap and water. Seek medical attention if irritation persists.	Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHA approved hydrocarbon canister or respirator when using in poorly ventilated areas. Ventilation Requirements: Provide mechanical exhaust to keep TLV of Section 2 ingredients below acceptable limit. Protective Gloves: Solvent proof rubber or neoprene. Eye Protection: Chemical splash goggles. Other Protective Equipment: Fire extinguisher should be located nearby when using. SECTION 9-SPILL OR LEAK PROCEDURES Steps to be taken in Case Material is Released or Spilled: Floors will become slippery. Avoid walking in product. Keep unessential personnel away. Mop up or				
Effects of Overexposure: Skin: Prolonged or repeated contact may cause irritation or dermatitis. Eyes: Eye irritant. May cause redness, swelling, or blurred vision. Inhalation: May cause dizziness or drowsiness. Ingestion: May cause dizziness, drowsiness or narcosis. Aspiration of material into the lungs can cause pneumonitis. First Aid Procedures: Skin: Remove contaminated clothing. Wash with soap and water. Seek medical	Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHA approved hydrocarbon canister or respirator when using in poorly ventilated areas. Ventilation Requirements: Provide mechanical exhaust to keep TLV of Section 2 ingredients below acceptable limit. Protective Gloves: Solvent proof rubber or neoprene. Eye Protection: Chemical splash goggles. Other Protective Equipment: Fire extinguisher should be located nearby when using. Steps to be taken in Case Material is Released or Spilled: Floors will become slippery. Avoid walking in product. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways.				
Effects of Overexposure: Skin: Prolonged or repeated contact may cause irritation or dermatitis. Eyes: Eye irritant. May cause redness, swelling, or blurred vision. Inhalation: May cause dizziness or drowsiness. Ingestion: May cause dizziness, drowsiness or narcosis. Aspiration of material into the lungs can cause pneumonitis. First Aid Procedures: Skin: Remove contaminated clothing. Wash with soap and water. Seek medical attention if irritation persists. Eyes: Flush with large quantities of water, holding eyelids open. Seek medical attention.	Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHA approved hydrocarbon canister or respirator when using in poorly ventilated areas. Ventilation Requirements: Provide mechanical exhaust to keep TLV of Section 2 ingredients below acceptable limit. Protective Gloves: Solvent proof rubber or neoprene. Eye Protection: Chemical splash goggles. Other Protective Equipment: Fire extinguisher should be located nearby when using. Steps to be taken in Case Material is Released or Spilled: Floors will become slippery. Avoid walking in product. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways. Waste Disposal Method: Any method in accordance with local, state and federal				
Effects of Overexposure: Skin: Prolonged or repeated contact may cause irritation or dermatitis. Eyes: Eye irritant. May cause redness, swelling, or blurred vision. Inhalation: May cause dizziness or drowsiness. Ingestion: May cause dizziness, drowsiness or narcosis. Aspiration of material into the lungs can cause pneumonitis. First Aid Procedures: Skin: Remove contaminated clothing. Wash with soap and water. Seek medical attention if irritation persists. Eyes: Flush with large quantities of water, holding eyelids open. Seek medical attention. Inhalation: Get to fresh air. If breathing is difficult, give oxygen. Seek medical	Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHA approved hydrocarbon canister or respirator when using in poorly ventilated areas. Ventilation Requirements: Provide mechanical exhaust to keep TLV of Section 2 ingredients below acceptable limit. Protective Gloves: Solvent proof rubber or neoprene. Eye Protection: Chemical splash goggles. Other Protective Equipment: Fire extinguisher should be located nearby when using. Steps to be taken in Case Material is Released or Spilled: Floors will become slippery. Avoid walking in product. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways. Waste Disposal Method: Any method in accordance with local, state and federal laws. Best method is to recycle or reuse for intended purpose. Consult local				
Effects of Overexposure: Skin: Prolonged or repeated contact may cause irritation or dermatitis. Eyes: Eye irritant. May cause redness, swelling, or blurred vision. Inhalation: May cause dizziness or drowsiness. Ingestion: May cause dizziness, drowsiness or narcosis. Aspiration of material into the lungs can cause pneumonitis. First Aid Procedures: Skin: Remove contaminated clothing. Wash with soap and water. Seek medical attention if irritation persists. Eyes: Flush with large quantities of water, holding eyelids open. Seek medical attention.	Respiratory Protection: Use with adequate ventilation. Use NIOSH/MSHA approved hydrocarbon canister or respirator when using in poorly ventilated areas. Ventilation Requirements: Provide mechanical exhaust to keep TLV of Section 2 ingredients below acceptable limit. Protective Gloves: Solvent proof rubber or neoprene. Eye Protection: Chemical splash goggles. Other Protective Equipment: Fire extinguisher should be located nearby when using. SECTION 9-SPILL OR LEAK PROCEDURES Steps to be taken in Case Material is Released or Spilled: Floors will become slippery. Avoid walking in product. Keep unessential personnel away. Mop up or otherwise absorb and hold disposal. Avoid discharge to sewer or open waterways. Waste Disposal Method: Any method in accordance with local, state and federal				

SECTION 10-REGULATORY INFORMATION					
SARA Title III - Section 311/312 -Hazard Categories: Shipping Information:		HMIS Hazardous Materials			
Yes - Fire Hazard	FOR CONTAINERS > 1 Gallon : Cleaning Compound	Identification System			
No - Sudden Release of Pressure Hazard		Health	1		
No - Reactivity Hazard	FOR 1 GALLON CONTAINERS : Cleaning Compound	Flammability	2		
Yes - Immediate (acute) Health Hazard		Reactivity	0		
No - Delayed (chronic) Health Hazard	FOR CONTAINERS < 1 GALLON : Cleaning Compound	Personal Protection	С		

FOR EMERGENCY MEDICAL OR TRANSPORT INFORMATION: ER# 1-888-779-1339

This product contains the following toxic chemical(s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

CAS#	Chemical Name	Percent by Weight		
	None			
This product contains the following chemical(s) which have been established to be either a carcinogen or suspected carcinogen.				
CAS#	Chemical Name	Percent by Weight		
	None			

SECTION 11-OTHER INFORMATION

This company cannot anticipate all conditions of handling and use of this product. Therefore, this company accepts no responsibility for results obtained by the application of this information, or the safety and suitability of our products either alone or in combination with other products. It is the responsibility of the user to provide a safe workplace, using the health and safety information contained herein as a guide. This company will accept no liability for damages or loss incurred from the improper handling and use of this product