

According to US Standard ANSI Z400.1-2004

Print date: 19-May-2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

SDS Number: EPA Submission SDS

Commercial Product Name: Professional Lysol® Brand III Kills 99.9% of Viruses & Bacteria

**Disinfectant Spray Crystal Waters Scent** 

Validation/Revision Date 19-May-2011

Product Identifier: EPA Reg. Number: 777-99-675

Formula Number: 1178-172 (0175917)

**UPC Code(s) and Size:** 36241-84044-0 (12.5 oz.)

Recommended use Disinfectant surface spray

Manufacturer: Reckitt Benckiser LLC.

Morris Corporate Center IV

399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225

Telephone: +1 973 404 2600

**Distributor:** Reckitt Benckiser LLC.

Morris Corporate Center IV

399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225

Telephone: +1 973 404 2600

**Emergency Telephone Number:** 1-800-228-4722 (U.S)

**Transportation Emergencies:** 1-800-424-9300 (U.S. & Canada) CHEMTREC

Outside U.S. and Canada (North America), call Chemtrec:703-527-3887



According to US Standard ANSI Z400.1-2004

## 2. HAZARDS IDENTIFICATION

## **Emergency Overview**

- CAUTION!

Causes moderate eye irritation.

DO NOT spray in eyes, on skin or on clothing.

Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco.

## FLAMMABLE.

Contents under pressure.

Keep away from heat, sparks, and open flame.

Do not puncture or incinerate container.

Exposure to temperatures above 130° F may cause bursting.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Proportion (% w/w)	ACGIH - Occupational Exposure Limits - TWAs	OSHA PEL
Ethanol 64-17-5	30 - 60 %		TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>
n-butane	1 - 5 %	= 1000 ppm TWA 1 322 1	TWA: 1900 mg/m <sup>3</sup>
106-97-8		Butane	TWA: 800 ppm
Propane	< 2.5 %	= 1000 ppm TWA 1 322 1	TWA: 1000 ppm
74-98-6		Propane	TWA: 1800 mg/m <sup>3</sup>



### According to US Standard ANSI Z400.1-2004

## 4. FIRST AID MEASURES

Inhalation Move to fresh air

Skin Contact Wash off immediately with soap and plenty of water removing all contaminated clothes and

shoes. If skin irritation persists, call a physician.

If in eyes, Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove **Eye Contact** 

contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison

Control Center or Doctor for treatment advice.

Ingestion Clean mouth with water and afterwards drink plenty of water. DO NOT INDUCE VOMITING.

Never give anything by mouth to an unconscious person. Call a physician or Poison Control

Center immediately.

Contains Denatured Ethyl Alcohol Notes to Physician

Ingestion may result in ethanol poisoning

Treat symptomatically

**Protection of First-aiders** Use personal protective equipment.

Aggravated Medical Conditions: NOTE TO PARENTS: Intentional misuse by deliberately concentrating and inhaling

aerosol products may be harmful or fatal. Help stop inhalation abuse; for information

visit www.inhalant.org.

## 5. FIRE-FIGHTING MEASURES

Flash point: 25.6°C (78°F)

Aerosol flame extension less than 18 inches (45 cm).

FLAMMABLE AEROSOL.

Suitable Extinguishing Media: Use water spray, dry chemical, CO2, or "alcohol" foam as suitable for the surrounding fire

conditions.

Unsuitable Extinguishing media: No information available

Unusual hazards: Aerosol cans may explode with extreme heat and become projectiles.

fighters

Special protective equipment for fire- As in any fire, wear self-contained breathing apparatus, pressure-demand, MSHA/NIOSH

(approved or equivalent) and full protective gear.

Precautions for fire-fighting Standard procedure for chemical fires. Move aerosol containers away from fire if possible

and safe to do so. Use water spray to cool fire exposed containers. Provide shielding to

protect firefighters from venting, rupturing or bursting containers.

Flammability Rating 1, per NFPA 30B. NFPA Aerosol Level:

NFPA: Health Hazard: 1 Flammability: 1 Instability / Reactivity 0 Special: --

Health Hazard: 1 Personal Protection: B HMIS: Flammability: 3 **Physical Hazard:** 0

(Also see Sections 3 & 8) Key:



According to US Standard ANSI Z400.1-2004

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Ensure adequate ventilation.

**Environmental Precautions:** Do not allow material to contaminate ground water system. Local authorities should be

advised if significant spillages cannot be contained.

Methods for Cleaning Up: Small spills: Wearing appropriate protective equipment, soak up with an inert absorbent

material and dispose of in an appropriate waste container. Rinse surface residue and flush

to sink or sanitary sewer.

Large Spills: Eliminate all sources of ignition and ventilate the area with equipment rated for

use in flammable environments.

Collect any remaining liquid and store in metal container for later disposal according to

local, state, provincial or federal regulations.

**Methods for Containment:** Prevent further leakage or spillage if safe to do so

## 7. HANDLING AND STORAGE

**Handling:** Use only as directed on the container label.

Ensure adequate ventilation Avoid breathing vapors or mists

Avoid contact with skin, eyes and clothing Wear personal protective equipment

Wash thoroughly with soap and water after handling and before eating, drinking, chewing

gum, using tobacco or using the toilet Do not puncture or incinerate cans

Keep product and empty container away from heat and sources of ignition.

Storage: Store in original container in areas inaccessable to small children and pets.

Store in cool/well-ventilated place

CONTAINERS SHOULD BE KEPT OUT OF REACH OF CHILDREN.

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding

55°C.

Do not pierce or burn after use. Keep away from all sources of ignition.

Fires involving flammable aerosols are severe and can spread very quickly. Warehouses and stores containing aerosols should therefore be separated from other areas by a fire

resistant construction of at least one half hour duration.

Stores should be well ventilated, particularily at low levels. The natural ventilation in a large

open warehouse building will normally be suitable.

Avoid the storage of aerosols in basesments where practicable.

This product must be stored and handled in accordance with the NFPA and local Fire Code

flammable liquids regulations.

EPA Registered Product: It is a violation of federal law to use this product in a manner inconsistent with its labeling.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name	ACGIH TLV	OSHA PEL
Ethanol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m³
04 17 3		1 WA. 1300 Hg/HF



According to US Standard ANSI Z400.1-2004					
n-butane 106-97-8	TWA: 1000 ppm	TWA: 1900 mg/m³ TWA: 800 ppm			
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>			

**Engineering Controls:** For occupational exposures, ensure adequate ventilation.

Environmental exposure controls Local authorities should be advised if significant spillages cannot be contained

**Personal Protective Equipment** 

**Respiratory Protection:** None required under normal usage.

Use only with adequate ventilation

Emergency responders should wear self-contained breathing apparatus (SCBA) to avoid inhalation of vapors generated by this product during a spill or other clean-up operations.

**Eye/Face Protection:** Avoid contact with eyes

Tightly fitting safety goggles

**Hand Protection:** Avoid contact with skin

Wear protective gloves/clothing.

Skin and Body Protection: Usual safety precautions while handling the product will provide adequate protection against

injury or irritation. Follow product label instructions.

**Hygiene Measures:** Avoid contact with eyes, skin, and clothing.

Wash thoroughly with soap and water after handling.



According to US Standard ANSI Z400.1-2004

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:Liquid.Appearance:Aerosol

Colour: Clear

Odour: Characteristic of variant

**pH** 10.5 - 11.8

Flash Point: 25.6°C / 78°F (Concentrate)

Flammability Limits in Air: No information available

Autoignition Temperature: No information available.

Specific Gravity / Density [g/mL]: 7.1 - 7.5 lbs/gal

Vapour pressure: not determined.

**Solubility:** Water solubility: completely soluble.

**Explosion limits:** 

- upper: No data available.- lower: No data available.

## 10. STABILITY AND REACTIVITY

Stability: Stable under recommended storage conditions. Stable up to 55 °C

Conditions to Avoid: Heat, flames and sparks.

Pressurised container. Protect from the sunlight and do not expose to temperatures exceeding 55° C (130° F). Extremes of temperature can occur in cars and near ovens and fireplaces. Do not place in contact with hot surfaces or near naked flames. Do not pierce or burn even after use. Do not spray on a naked flame, onto or near fire, or any incandescent

material such as an electric fire.

Materials to Avoid: Do not mix with other household chemicals

Hazardous Decomposition Products: Oxides of carbon and unknown organic compounds.

Thermal decomposition can lead to release of irritating gases and vapors

**Polymerization:** Hazardous polymerization does not occur.



## According to US Standard ANSI Z400.1-2004

## 11. TOXICOLOGICAL INFORMATION

## PRODUCT TOXICITY DATA

LD<sub>50</sub> Oral: No information available

 $LD_{50}$  Dermal: No information available  $LC_{50}$  Inhalation (Dust): No information available  $LC_{50}$  Inhalation (Vapor): No information available

**ACUTE EFFECTS** 

**Eye Irritation** Moderate eye irritation

**Skin Irritation** None expected during normal conditions of use.

Inhalation None expected during normal use. However intentional misuse by deliberately

concentrating and inhaling the contents may be harmful or fatal.

**Ingestion** Contains denatured ethyl alcohol.

May be harmful if swallowed.

See Section 4 for First Aid instructions.

**Sensitization** Not expected to be a skin sensitiser.

Chronic Effects No information available...

**Specific Effects** 

Carcinogenic Effects: Not listed as carcinogenic by OSHA, NTP or IARC.

Mutagenic EffectsNo information available.Reproductive Toxicity:No information available.

Additional Toxicity Information: Information is based on available component data and toxicity result of similar products.

### **COMPONENT TOXICITY DATA**

Chemical Name	CAS-No	LD50 Oral - with units - Rat - mg/kg	LD50 Dermal - With Units - Rat/Rabbit - mg/kg	LC50 Inhalation - With units - Rat/Rabbit
Ethanol	64-17-5	7060 mg/kg (Rat)	no data available	no data available
n-butane	106-97-8	no data available	no data available	658 mg/L (Rat) 4 h
Propane	74-98-6	no data available	no data available	658 mg/L (Rat) 4 h



According to US Standard ANSI Z400.1-2004

## 12. ECOLOGICAL INFORMATION

PRODUCT TOXICITY DATA

**Ecotoxicity effects:** No data is available on the product itself.

Aquatic toxicity: No information available

COMPONENT TOXICITY DATA

Ethanol

64-17-5 (30 - 60 %)

Freshwater Fish LC50 96 h Oncorhynchus mykiss 12.0-16.0 ml/L

LC50 96 h Pimephales promelas >100 mg/L

LC50 96 h Pimephales promelas 13400-15100 mg/L

**Microtox** EC50 = 35470 mg/L 5 min **Water Flea**  $LC50 \ 48 \ h \ 9268 - 14221 \ \text{mg/L}$ 

EC50 24 h 10800 mg/L EC50 48 h 2 mg/L

**Other Information** 

Ozone depletion potential; ODP;

No information available.

(R-11 = 1)

Global Warming Potential (GWP): No information available.

Additional Ecological Information: Information given is based on data on the components and the

ecotoxicology of similar products.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused

products:

Dispose of in accordance with local, state and federal regulations.

Contaminated Packaging: Do not re-use empty containers. DO NOT PUNCTURE OR INCINERATE! Dispose of

empty container in household trash.

Waste Disposal: Container disposal: Empty containers may be included with domestic refuse for disposal to a

landfill. This container may also be recycled in communities where aerosol container recycling is available. Before offering for recycling, empty the can or use the product

according to the label instructions.



## According to US Standard ANSI Z400.1-2004

## 14. TRANSPORT INFORMATION

For long distance transport of bulk material or shrunk pallet take into consideration General remarks

sections 7 and 10.

DOT

Consumer Commodity Proper shipping name:

UN-No: UN1950 **Hazard Class** Not applicable **Subsidiary Class** Not applicable Packing group: Not applicable Reportable Quantity (RQ): Not applicable

Description: UN 1950, Aerosols, Class 2.1

Re-classed as Consumer Commodity ORM-D

Emergency Response Guide No:126 / 171

**TDG** 

Proper shipping name: Consumer Commodity/LTD. QTY

UN-No: UN1950

Not applicable Packing group:

**Description:** UN 1950, Aerosols, Class 2.1

Re-classed as Consumer Commodity ORM-D

MEX Not applicable.

**ICAO** See IATA

**IATA** 

UN-No: UN1950

Proper shipping name: Aerosols, flammable \Consumer Commodity **Hazard Class** 2.1 / (9 if shipped as a Consumer Commodity)

**Subsidiary Class** Not applicable Packing group: Not applicable

Description: UN1950, Aerosols, flammable, Limited Quantity or Consumer Commodity, ID8000 if

acceptable to airline.

See DG List. **Maximum quantity** 

IMDG/IMO

**Proper Shipping Name** Aerosols **Hazard Class** 

**Subsidiary Risk:** 

Not applicable **UN-No** UN1950 **Packing Group** Not applicable **IMDG Page:** See IMDG Code. **Marine Pollutant** Not applicable F-D. S-U EmS: MFAG: Not applicable. See IMDG Code. Maximum quantity:

RID Not applicable.

**ADR** Not applicable.

Validation/Revision Date SDS Number: Version No.: Commercial Product Name: Page 9 of 11



## According to US Standard ANSI Z400.1-2004

ADN Not applicable.

## 15. REGULATORY INFORMATION

Chemical Name	PICCS	TSCA	DSL	NDSL	ENCS	CHINA	AICS	EINECS/ ELINCS	South Africa STELs
Ethanol		Present	X		Χ	X	Х	200-578-6	
n-butane		Present	X		Χ	X	Х	203-448-7	
Propane		Present	X		Х	X	Х	200-827-9	

### U.S. Regulations:

Ethanol - 64-17-5

**NJRTK** X

Appearance Colorless, clear, volatile liquid

SARA313 None

California Prop. 65 Not listed for non-beverage applications.

n-butane - 106-97-8

NJRTK )

Appearance Colorless gas SARA313 None California Prop. 65 Not Listed

Propane - 74-98-6

NJRTK X

Appearance Colorless gas SARA313 None California Prop. 65 Not Listed

WHMIS (Canada)

WHM IS Hazard Class B5 Flammable aerosol



## According to US Standard ANSI Z400.1-2004

## 16. OTHER INFORMATION

**National Fire Protection Association** (U.S.A.):



HMIS (U.S.A.):

Health Hazard	1
Flammability:	3
Physical hazards	0
Personal Protection	В

NFPA Aerosol Level: Flammability Rating 1, per NFPA 30B.

Reason for revision: This is a SDS for EPA Registration, not to be used for distribution with the final retail product.

Additional advice: This product should only be used as directed on the label and for the purpose intended.

Prepared by: Reckitt Benckiser LLC.

Product Safety Department

1 Philips Parkway

Montvale, New Jersey 07646-1810 USA.

FAX: 201-476-7770

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.