

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 500
IDENTITY: D-GREAZE

Revision Date: 02/11/2009

Section I

Manufacturer's Name:QUEST CHEMICAL CORPORATION Telephone Numbers:
Address: 12255 FM 529 Emergency:
NORTHWOODS INDUSTRIAL PARK 800/255-3924
HOUSTON Information:
State: TX Zip Code:77041 713/8968188

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 2 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Rows include 1,8-P-MENTHADIENE, CARBON DIOXIDE, ISOPARAFINIC HYDROCARBON, and PROPANE.

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT
TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING
AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: 352 F Specific Gravity (water=1) 0.85
Vapor Pressure(mm Hg) 2 Melting Point: N/A
Vapor Density(AIR=1) 4.7 Evaporation Rate: < 1
Solubility in Water: SLIGHT (Butyl Acetate=1)
Appearance and Odor: CLEAR WATER WHITE LIQUID, CITRUS ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used):122F TCC Flammable Limits: LEL:.7 UEL: 6.1
Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER
Special Fire Fighting Procedures: CLASS B FIRE PROCEDURES

Unusual Fire and Explosion Hazards: COMBUSTIBLE LIQUID. KEEP AWAY FROM HEAT,
SPARKS, AND OPEN FLAMES. TEMPERATURES >120 F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 500

Stability: Unstable: Conditions to avoid: TEMPERATURES >120F
Stable: X
Incompatibility (Materials to Avoid): STRONG OXIDIZING AGENTS

Hazardous Decomposition or Byproducts: NONE

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: EXCESSIVE EXPOSURE CAN CAUSE DIZZINESS. SKIN & EYES: WILL DEFAT
AND IRRITATE EYES AND SKIN. INGESTION: WILL CAUSE NAUSEA AND/OR DIARRHEA.

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE VICTIM TO FRESH AIR
SKIN: RINSE WITH SOAP AND WATER. EYES: RINSE WITH WATER FOR 15 MINUTES.
INGESTION: GIVE SMALL GLASS OF WATER OR MILK. DO NOT INDUCE VOMITING. SEE
PHYSICIAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: REMOVE ANY
SOURCE OF HEAT, FLAME, OR SPARKS. EVACUATE AFFECTED AREA. MOP UP WITH
APPROPRIATE ABSORBENT MATERIAL. AVOID BREATHING FUMES VENTILATE AREA.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL,
STATE AND LOCAL REGULATIONS.

Precautions to be Taken in Handling and Storing: KEEP AWAY FROM HEAT,
SPARKS AND FLAME. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION.
STORE IN ACCORDANCE WITH NEPA, STATE AND LOCAL GUIDELINES.

Other Precautions: AVOID PROLONGED OR REPEATED INHALATION OF MIST OR VAPOR
AND CONTACT WITH SKIN. EXPOSURE TO TEMPERATURES >120 F MAY CAUSE BURSTING.

Section VIII: CONTROL MEASURES

Respiratory Protection: NOISH APPROVED RESPIRATOR PROTECTION IF NEEDED.

Ventilation: Local Exhaust: SUFFICIENT

Mechanical: N/A

Special: N/A

Other: N/A

Protective Gloves: N/A

Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.

Other Protective Clothing or Equipment:

N/A

Work/Hygienic Practices:

WASH HANDS AFTER USE.

□