

Material Safety Data Sheet

Product Name	METALIST™ FLOOR SEALER	MSDS#	Not available.	
Product Description	Acrylic Floor Seal Formerly Known As: Duration™ Floor Seal.	Validation Date 5/30/2000		
	· · · · · · · · · · · · · · · · · · ·	Print Date	1/15/2001	
Manufacturer	Reckitt Benckiser Inc. 1655 Valley Road			
	Wayne, N.J. 07474	In case of	Telephone: 800-677-9218	
Product Identifier	Not a∨ailable.	Emergency:	(Professional Products)	
Item Number	358833	Transportation Emergencies:		
Formula Number	394-106		·	
UPC Number	36241-74460 (1 gal.), 36241-04901, (1 gal.), 36241-04905 (5 gal.), 36241-04955 (55 gal. drum)			

Section 2. Composition and Information on Ingredients			
Name	CAS#	% by Weight	Exposure Limits : TLV/PEL
1) DIETHYLENE GLYCOL MONOETHYL ETHER	111-90-0	4.0	Not available.

Section 3. Hazards identification			
Emergency Overview	KEEP OUT OF REACH OF CHILDREN		

Section 4. First Aid Measures		
Eye Contact	As with any material contacting the eye, it is recommended to rinse the eyes thoroughly with water.	
Skin Contact	In keeping with good hygienic practices, wash thoroughly with soap and water.	
Inhalation	None normally required. Remove to fresh air.	
Ingestion	on Rinse mouth with water. Contact a physician or poison control center if symptoms develop.	

Section 5. Fire and Explosion Data		
Flammability	Not flammable. See Section 14 for any Shipping Classifications.	
Flash Point	CLOSED CUP: Higher than 93.3°C (>200°F). (Tagliabue.).	
Explosive Limits in Air	Not available.	
Products of Combustion	Not available.	
Fire and Explosion Hazards	None known.	
Fire Fighting Media and Instructions		
Special Fire Fighting Instructions	Wear self-contained breathing apparatus and protective clothing appropriate for fighting a typical chemical fire.	

Continued on Next Page

Section 6. Accidental Release Measures

Accidental Spill Small spills: Dilute with water and mop up, or absorb with an inert material and place in an appropriate waste

disposal container.

Large spills should be diked, contained and collected for later disposal according to local, state or federal regulations.

Section 7. Handling and Storage

Handling and Storage KEEP OUT OF REACH OF CHILDREN.

Store in a cool, dry location. Keep from freezing. Do not pour unused product back into container.

WARNING: Child can fall into 5 gal. bucket and drown. Keep children away from 5 gallon buckets with even a small amount of liquid.

Section 8. Exposure Controls/Personal Protection

Ventilation Requirements None required.

Eye Protection None required.

Skin Protection None required.

Respiratory Protection None required.

Other Protection None required.

Work/Hygienic Practices None required.

Section 9. Physical and Chemical Properties

Description	Clear to slightly hazy liquid.	Odor	Acrylic odor.
рН	8.6 [Basic.]	Color	Off-white.
B 411 42 1 4 B 4 4			

Boiling/Condensation Point Not determined.

Specific Gravity 1.023

Vapor Pressure Not determined.

Vapor Density >1

Viscosity Not available.

Solubility Miscible.

Physical Chemical Comments Not available.

Section 10. Stability and Reactivity Data

Chemical Stability The product is stable.

Conditions of Instability None known.

Incompatibility with Various Acids.

Substances

nces

Hazardous Decomposition Products

None known.

Continued on Next Page

METALIST™ FLOOP	R SEALER	Page Number: 3
Hazardous Polymerization	Will not occur.	
Section 11. Toxicolo	gical Information	
Exposure effects		
Eye Contact	None known.	
Skin Contact	None known.	
Inhalation	None known.	
Ingestion	None known.	
Carcinogenicity	Not listed as carcinogenic by OSHA, NTP or IARC.	
Section 12. Ecologic	al Information	
Ecotoxicity	Not available.	
Section 13. Disposal	Considerations	
Waste Disposal	The disposal of the product must be made in accordance with all governmental regulation	ns.
Section 14. Transpor	t Information	
DOT Classification	Not a DOT controlled material (United States).	
Proper Shipping Name	Not applicable.	_
DOT Identification Number	Not applicable.	
Packing Group	Not applicable.	
Maritime Transportation	Not available.	
Hazardous Substances Reportable Quantity	Not available.	
Special Provisions for Transport	Not available.	
TDG Classification	Not a TDG controlled material.	
ADR Classification	Not available.	
IMDG Classification	Not controlled under IMDG.	

Not controlled under IATA.

IATA Classification

Section 15. Regulatory Information Federal and State Regulations SARA Title III, Section 313 Toxic Chemical Notification & Release Reporting: 1) DIETHYLENE GLYCOL MONOETHYL ETHER CAS #: 111-90-0 4.0 % California Proposition 65: This product contains the following ingredients which require a warning under the Safe Drinking Water & Toxic Enforcement Act: 1) Not available. WHMIS (Canada) Not controlled under WHMIS (Canada).

Page Number: 4

Section 16. Other Information Health Hazard Fire Hazard HMIS (U.S.A.) **National Fire Protection** 0 Association (U.S.A.) Fire Hazard Reactivity 0 0 Health $\mathbf{0}$ Rescuvity Specific hazard **Personal Protection** a NFPA Aerosol Level Not applicable. Validated by Product Safety on 5/30/2000. Printed 1/15/2001.

Notice to Reader

METALIST™ FLOOR SEALER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.