# MATERIAL SAFETY DATA SHEET



Version Number: 4

### **1. PRODUCT AND COMPANY IDENTIFICATION**

Product name: MSDS #: Product Code: Recommended use: CROWBAR Ultra Stripper MS0400132 4973900 Industrial/Institutional. Floor care. This product is intended to be diluted prior to use.

Manufacturer, importer, supplier:

US Headquarters Diversey, Inc. 8310 16th St. Sturtevant, Wisconsin 53177-1964 Phone: 1-888-352-2249 MSDS Internet Address: www.diversey.com Canadian Headquarters Diversey, Inc. - Canada, Inc. 2401 Bristol Circle Oakville, Ontario L6H 6P1 Phone: 1-800-668-3131

**Emergency telephone number:** 

1-800-851-7145 (U.S.); 1-651-917-6133 (Int'l)

### 2. HAZARDS IDENTIFICATION

#### **EMERGENCY OVERVIEW**

- DANGER
- CORROSIVE
- CAUSES SKIN AND EYE BURNS
- HARMFUL OR FATAL IF SWALLOWED


Principal routes of exposure:	Eye contact. Skin contact. Inhalation.
Eye contact:	Corrosive. Causes permanent eye damage, including blindness.
Skin contact:	Corrosive. Causes permanent damage.
Inhalation:	May cause irritation and corrosive effects to nose, throat and respiratory tract.
Ingestion:	Corrosive. Causes burns to mouth, throat and stomach.

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Ingredient(s)	CAS #	Weight %
Benzyl alcohol	100-51-6	10 - 25%
2-butoxyethanol	111-76-2	5 - 10%
Sodium hydroxide	1310-73-2	1 - 5%
Monoethanolamine	141-43-5	10 - 25%

### 4. FIRST AID MEASURES

Eye contact:	Immediately flush eyes with running water for 15-20 minutes, keeping eyelids open. Get medical attention immediately.
Skin contact:	Immediately flush with plenty of water for 15-20 minutes . Get medical attention immediately.
Inhalation:	If breathing is affected, remove to fresh air. Get medical attention immediately.
Ingestion:	If swallowed, rinse mouth. Give a cupful of water or milk . THEN IMMEDIATELY CONTACT A PHYSICIAN OR POISON CENTER. DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
Aggravated Medical Conditions:	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects





## **5. FIRE-FIGHTING MEASURES**

#### Suitable extinguishing media:

The product is not flammable. Extinguish fire using agent suitable for surrounding fire.

**Extinguishing media which must not be used for safety reasons:** No information available

#### Special protective equipment for firefighters:

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

#### Specific hazards: Not applicable

**Unusual hazards:** Corrosive material (See sections 8 and 10). **Specific methods:** No special methods required

<b>NFPA</b> Health 3	Flammability 0	Instability 0
6. ACCIDENTAL RELEAS	SE MEASURES	
Personal precautions:	Put on appropriate personal protective equipment (see Section	ion 8.).
Environmental precautions and clean-up methods:	Use appropriate containment to avoid environmental contar (e.g. dry sand or earth), then place in a chemical waste cont	

containers for disposal. Use a water rinse for final clean-up.

### 7. HANDLING AND STORAGE

Handling:	Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.
Storage:	Protect from freezing. Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.

### Personal Protective Equipment

Eye p	protection:	Chem	ical-splash goggles.			
Hand	protection:	Chem	ical-resistant gloves			
Skin	and body protection:	Protec	tive footwear. If major expos	sure is possible, we	ear suitable protective clothin	ng and footwear.
Resp	iratory protection:	In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.		• •		
Hygie	ene measures:	Handl	e in accordance with good inc	lustrial hygiene and	d safety practice	
HMIS	Health	3	Fire Hazard	0	Reactivity	0



### Personal protective equipment

Ingredient(s)	ACGIH	OSHA	Mexico
2-butoxyethanol	20 ppm (TWA)	Skin	75 ppm (STEL) 360 mg/m3 (STEL)
		50 ppm (TWA) 240 mg/m3 (TWA)	26 ppm (TWA) 120 mg/m3 (TWA)
Sodium hydroxide	2 mg/m <sup>3</sup> (Ceiling)	2 mg/m <sup>3</sup> (TWA)	2 mg/m <sup>3</sup> (Ceiling)

Monoethanolamine	6 ppm (STEL)	3 ppm (TWA) 6 mg/m <sup>3</sup> (TWA)	6 ppm (STEL) 15 mg/m3 (STEL)
	3 ppm (TWA)		3 ppm (TWA) 8 mg/m <sup>3</sup> (TWA)

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid	Color: Clear Colorless
Appearance: Liquid	Odor: Glycol Ether
Specific gravity: 1.05	Density: 8.76 lbs/gal 1.05 Kg/L
Bulk density: No information available	Vapor density: No information available
Viscosity:No information available	Evaporation Rate No information available
Solubility: Completely Soluble	<b>VOC:</b> 24.9 % *
рН: 13.2	Dilution pH: 12.34 @ 1:4
Solubility in other solvents: No informat	ion available
Partition coefficient (n-octanol/water):	No information available
Explosion limits:	

Boiling point/range:	Not determined		
Melting point/range:	Not determined		
Flash point:	> 200 °F > 93.4 °C		
Decomposition temperature:	Not determined		
Autoignition temperature:	No information available		
Elemental Phosphorus:	0 % by wt.		

\* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

## **10. STABILITY AND REACTIVITY**

Stability:	The product is stable
Polymerization:	Hazardous polymerization does not occur
Materials to avoid:	Acids. Strong oxidising agents.
Conditions to avoid:	Do not mix with any other product or chemical .
Hazardous decomposition products:	None reasonably foreseeable.

# 11. TOXICOLOGICAL INFORMATION

Ingredient(s)	LD50 Oral - Rat (mg/kg)	LD50 Dermal - Rabbit	LC50 Inhalation - Rat
Benzyl alcohol	1230	2000 mg/kg	8.8 mg/L (4 h)
2-butoxyethanol	1400	220 mg/kg	2.21 mg/L (4 h) 450 ppm (4 h)
Sodium hydroxide	500	1350 mg/kg	Not available
Monoethanolamine	1720	1 mL/kg 1025 mg/kg	Not available

Acute toxicity:

Corrosive Oral LD50 estimated to be between 1000 - 2000 mg/kg  $\,$  Dermal LD50 estimated to be > 2000 mg/kg  $\,$  None known

Chronic toxicity:

Specific effects

Carcinogenic effects:	None known
Mutagenic effects:	None known
<b>Reproductive toxicity:</b>	None known
Target organ effects:	None known

# **12. ECOLOGICAL INFORMATION**

#### **Environmental Information:**

No data available

### **13. DISPOSAL CONSIDERATIONS**

#### Waste from residues / unused products:

Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of in compliance with all Federal, state, provincial, and local laws and regulations.

# **14. TRANSPORT INFORMATION**

DOT/TDG/IMDG: Please refer to the Diversey HazMat Library, http://naextranet.diversey.com/dot/, for up to date shipping information.

### **15. REGULATORY INFORMATION**

#### International Inventories at CAS# Level

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

#### **U.S. Regulations**

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

#### Right To Know (RTK)

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
Benzyl alcohol	100-51-6	Х	-	Х	-
2-butoxyethanol	111-76-2	Х	Х	Х	Х
Sodium xylene sulfonate	1300-72-7	-	-	-	-
Sodium hydroxide	1310-73-2	Х	Х	Х	Х
Monoethanolamine	141-43-5	Х	Х	Х	Х
Water	7732-18-5	-	-	-	-

#### CERCLA/ SARA

<b>Ingredient</b> (s)	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
2-butoxyethanol 111-76-2	5 - 10%			Х
Sodium hydroxide 1310-73-2	1 - 5%	1000		

Component	CAA HAP	CAA ODS	CWA Priority Pollutants
2-butoxyethanol	Х		
111-76-2 (5 - 10%)			

#### SARA 311/312 Hazard Categories

Immediate:	Х
Delayed:	-
Fire:	-
Reactivity:	-
Sudden Release of Pressure:	-
Canada	



WHMIS hazard class: E Corrosive material

# **16. OTHER INFORMATION**

**Reason for revision:** 

Not applicable

None

Prepared by: NAPRAC

Additional advice:

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.