MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANU	JFACTU	RER'S INFORMATIO	N				
NFPA Rating: Health-2; Flammability-0; Reactivity-0; Special HMIS Rating: Health-2; Flammability-0; Reactivity-0; Personal Protection-B							
	DOT Hazard Classification: ORM-D						
	Identity (trade name as used on label):						
Address: Billerica, MA 01862	SSS Safety Solvent (aerosol) #05019						
	MSDS Number: A00365 Revision- 15						
	Date Prepared: 07/1/05 Prepared By: LF/DL/IB Information Calls: (978) 667-7900						
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION COMPONENTS-CHEMICAL NAMES AND COMMON NAMES CAS Number SARA OSHA PEL ACGIH Carcinogen							
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **	
PERCHLOROETHYLENE		127-18-4	Yes	25	25	a,b	
ACETONE							
CARBON DIOXIDE		67-64-1	No	1000	750	d	
CARBON DIOXIDE		124-38-9	No	5000	5000	d	
WARNING: This product contains a chemical or chemicals known							
to the State of California to cause cancer.							
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS							
Boiling Point: N/A							
Vapor Pressure: PSIG @ 70°F (Aerosols): 85-100	. , , , , ,						
Vapor Density (Air = 1): N/E							
Solubility in Water: Insoluble Water Reactive: No							
Appearance and Odor: Clear, colorless spray with chlorinated solvent odor.							
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA							
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) NON-FLAMMABLE	Auto Igr	to Ignition Temperature Flammability Limits in Air by % in Volume: N/E % LEL: N/E % UEL: N/E					
FLASH POINT AND METHOD USED (non-aerosols): N/A EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.							
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing							
apparatus.							
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.							
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NO					I I NOT		
[X] ONDEE [] ONOMBEE	OCCUR						
Incompatibility (Mat. to avoid): Reactive metals, aluminum,	onditions to Avoid: Open flame, welding arcs, heat.						
magnesium, strong oxidizing agents.							
Hazardous Decomposition Products: CO2, CO, HCl, small amounts of phosgene and chlorine.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS							
ACUTE EFFECTS:							
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.							
Eye Contact: Irritation Skin Contact: Irritation due to defatting of skin.							
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.							
CHRONIC EFFECTS:(Effects due to excessive exposure to the raw materials of this mixture) May cause liver abnormalities, kidney, spleen, lung or brain							
damage, cardiac abnormalities. Perchloroethylene has been shown to increase the rate of spontaneously occurring malignant tumors in certain laboratory rats							
and mice.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.							
Skin Contact: Wash with soap and water. If irritated, seek medical attention.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.							
SECTION 6 - CONTROL AND PROTECTIVE MEASURES							
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.							
Protective Gloves: Neoprene gloves recommended. Eye Protection: Safety glasses recommended.							
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.							
Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE							
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations.							
Allow to evaporate if small spill. DO NOT FLUSH TO SEWER.							
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.							
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.							
TOTHER PRECAUTIONS 6/OF SDECIAL MAZARDS: KEEP OUT OF REACH OF C	Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN, Avoid food contamination, Avoid inhalation of vapors.						