MATERIAL SAFETY DATA SHEET
This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

This MSDS complies with OSHA'S Hazard Co				and OSHA FO	IIII 174		
		TURER'S INFORMA		4.0. D	. O. D	I Destantia - D	
NFPA Rating: Health-1; Flammability-3; Reactivity-0; Special		HMIS Rating: Health-1; Flammability-3; Reactivity-0; Personal Protection-B					
Manufactured For: Triple S	l l	T Hazard Classifica					
Address: 2 Executive Park Dr.	lde	Identity (trade name as used on label):					
Address: Billerica, MA 01803		SSS Odor Neutralizer #05233					
		With Spray Thru Cap					
Phone: 978-667-7900		MSDS Number: A00207 Revision-4B (extremely flammable)					
Emergency Medical Information: 1-888-779-1339 Date Prepared: 03/30/10 (02/01/07) Prepared by: IB						l by: IB	
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA	Info	rmation Calls: (770)422	2-2071				
SECTION 1 - MATERIAI	L IDENTI	FICATION AND INF	ORMATI	ON			
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES		CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)			III LIST	(ppm)	TLV (ppm)	Ref. Source **	
ACETONE		67-64-1	No	1000	750	d	
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d	
		74-98-6	No	1000	1000	d	
SECTION 2 - PHYSIC	VI /CHE	MICAL CHARACTE	PISTICS	l	l l		
Boiling Point: N/A					Ω		
Vapor Pressure: PSIG @ 70°F (Aerosols): <b>50-6</b> 0		Specific Gravity (H2O=1): Concentrate Only = 0.8  Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A					
Vapor Pressure: PSIG @ 70°F (Aerosois): 50-60  Vapor Density (Air = 1): N/E		Evaporation Rate ( = 1): N/E					
Solubility in Water: Soluble  Water Reactive: No							
Appearance and Odor: Clear liquid with fragrance.	vvat	ei iteactive. NO					
	ANDEV	PLOSION HAZARD	DATA				
		Auto Ignition Temp		Florenski	litu I impito in Ai	r by 0/ in Maluman	
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosc		N/E	perature	% LEL:		r by % in Volume: % UEL: N/E	
flame projection with spray through cap: projection greater than 18	3" with	IN/E		70 LEL. I	N/ ⊑	76 UEL. IN/E	
flashback: Categorized as EXTREMELY FLAMMABLE							
		FIRE FIGHTING PROC					
		breathing apparatus. Co			tog to prevent	rupturing & spewing.	
Unusual Fire & Explosion Hazards: Do not expose aerosols to tempera				ture.			
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [ X ] STABLE [ ] UNSTABLE HAZARDOUS POLYMERIZATION [ ] WILL [ X ] WILL NOT OCCUR							
Incompatibility (Mat. to avoid): Alkalis, oxidizing materials, amines.  Conditions to Avoid: Open flame, welding arcs, heat.							
Hazardous Decomposition Products: CO, CO2.							
SECTION 5	- HEAL	TH HAZARD DATA	A				
PRIMARY ROUTES OF ENTRY: [ X]INHALATION [ ]INGESTION [ ]SKIN ABSORPTION [ ]EYE [ ]NOT HAZARDOUS							
ACUTE EFFECTS Vapor concentrations around 1000 ppm may cause slight transient irritation to the upper respiratory tract.							
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible							
unconsciousness.	iy cause	ricadacric, dizziricss	, aspriyai	a, anconicue	, chects and	possible	
Eye Contact: Irritation.	C Li	n Contact: May car	ico cliabt	irritation			
, ,							
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.							
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause mucous membrane irritation, overnight							
headache, and general weakness.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek me	edical att	ention.					
Skin Contact: Wash with soap and water. If irritated, seek medic							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention. Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.							
				tention.			
SECTION 6 - CONTR							
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH or U.S. Bureau of Mines for organic vapor.							
Protective Gloves: Latex, if skin easily irritated. Eye Protection: Safety glasses recommended.							
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.							
Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE							
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suita FLUSH TO SEWER.	ble mediu	m. Incinerate or landfill	according	to local, state	or federal reg	ulations. DO NOT	
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.							
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 120°F.							
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF C						gnition sources.	
We believe the statements, technical information and recommendations					,		
** Chamical Listed as Carolingan or Potential Carolinga							

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only