## **MATERIAL SAFETY DATA SHEET**

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

	The mess complies that control again community	pation otaniaara 20 on 11 ro	1011200 an	4 0 01 11 11 011			
	IDENTITY AND DISTRIBUTOR'S INFORMATION						
NFPA Rating: Health-1; Flammability-3; Reactivity-0; Special HMIS Rating: Health-1; Flammability-3; Reactivity-0; Personal Protection-B							
Manufactured For:	Triple S	DOT Hazard Classification: ORM-D					
Address:	2 Executive Park Dr.	Identity (trade name as used on label):					
Address:	Billerica, MA 01862	SSS Sunshine Air Deodorizer #05227					
Phone:	MSDS Number: A00239NF SB Revision-5 (NF)						
		Date Prepared: 02/01/07 Prepared By: TR / IB					
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA Information Calls: 978-667-7900							
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION							
	AL NAMES AND COMMON NAMES	CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)  ACETONE		07.04.4	III LIST	(ppm)	TLV (ppm)	Ref. Source **	
ISOBUTANE / PROPANE BLEND		67-64-1	No	1000	750	d	
ISOBUTANE / PROPANE BLEND		75-28-5	No	800	800	d	
		74-98-6	No	1000	1000	d	
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS							
Boiling Point: N/A		Specific Gravity (H2O=1): Concentrate Only = < 1					
Vapor Pressure: PSIG (	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A						
Vapor Density (Air = 1):	Evaporation Rate ( = 1): N/E						
Solubility in Water: Soluble Water Reactive: No							
Appearance and Odor: Clear liquid with fragrance.  SECTION 3 - FIRE AND EXPLOSION HAZARD DATA							
ELAMMARILITY as par LL	SA FLAME PROJECTION TEST (aerosols): flame	Auto Ignition Temperati		ammahility Li	mite in Air by 0	/ in Volume:	
projection with regular spr flashback: CPSC: <b>Not ca</b> t	Auto Ignition Temperature Flammability Limits in Air by % in Volume:  N/E						
	HOD USED (non-aerosols): N/A	SPECIAL FIRE FIGHTING	PROCED	URES: Provid	le shielding for	personnel. Wear	
	self-contained breathing apparatus. Cool containers with water fog to prevent						
EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water. rupturing & spewing.							
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 120°F or the container may rupture.							
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [X] STABLE [ ] UNSTABLE HAZARDOUS POLYMERIZATION [ ] WILL [X] WILL NOT OCCUR							
Incompatibility (Mat. to avoid): Alkalis, oxidizing materials, amines. Conditions to Avoid: Open flame, welding arcs, heat.							
Hazardous Decomposition Products: CO, CO2.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION []SKIN ABSORPTION []EYE []NOT HAZARDOUS							
ACUTE EFFECTS Vapor concentrations around 1000 ppm may cause slight transient irritation to the upper respiratory tract.							
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness.							
Eye Contact: Irritation	1	Skin Contact: May ca	uca eliaht	irritation			
Eye Contact: Irritation. Skin Contact: May cause slight irritation.  Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.							
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause mucous membrane irritation, overnight							
headache, and general weakness.  Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.							
Skin Contact: Wash with soap and water. If irritated, seek medical attention.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.							
SECTION 6 - CONTROL AND PROTECTIVE MEASURES							
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines/ NIOSH for organic vapor.							
Protective Gloves: Latex, if skin easily irritated.  Eye Protection: Safety glasses recommended.							
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.							
Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE							
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT							
FLUSH TO SEWER.	e: Aerosol cans when vented to atmospheric pressure thr	ough normal use, nose no	dienocal ba	zard			
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.  Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 120°F.							
Precautions 10 be taken in nanding & storage: Do not policiture of internetae containers. Do not store at temperatures above 120 P.							

her Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

\*\* Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only