SYS 203

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

This mode compiles with Collin a Hazard Community		The second secon	- FIRST THE CONTRACTOR	OSHA FORM T	19:		
IDENTITY AND DISTRIBUTOR'S INFORMATION							
NFPA Rating: Health-2; Flammability-2; Reactivity-0; Special-0		HMIS Rating: Health-2; Flammability-2; Reactivity-0; Personal Protection-B					
Manufactured For: Lagasse Brothers, Inc.		DOT Hazard Classification: ORM-D					
Address: 1525 Kuebel Street	lder	Identity (trade name as used on label):					
Address: New Orleans, LA 70123	-	System Clean Furniture Polish/ SYC2030					
Phone: 800-989-7487		MSDS Number: A00136 Revision- 3					
Emergency Response Number: 1-800-255-3924	11 CA	Date Prepared: 04/12/93 Prepared By: ES/KD					
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA		mation Calls: (770)422					
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION							
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES		CAS Number	SARA	OSHA PEL	ACGIH	Carcinogen Ref. Source **	
(Hazardous Components 1% or greater; Carcinogens 0.1% or greater) PETROLEUM DISTILLATE		0050 41 2	III LIST	(ppm)	TLV (ppm) 100	Nei, Source	
ISOBUTANE / PROPANE BLEND		8052-41-3	No	100	800	d	
ISOSOTANE / FROMANE BLEND		75-28-5	No	800 1000	1000	<u> </u>	
		74-98-6	No	1000	1000	u u	
			-				
			ļ —				
CECTION O DUNCHON JOHENNON OUADACTEDICTICS							
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS Specific Gravity (H2O=1): Concentrate Only = 0.980							
Boiling Point: N/A Vapor Pressure: PSIG @ 70°F (Aerosols): Max.60	The state of the s						
Vapor Density (Air = 1): N/E		Evaporation Rate (= 1): N/E					
Solubility In Water: Partial		Water Reactive: No					
Appearance and Odor: Cream color, with lemon fragrance.							
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA							
FLAMMABILITY as per USA FLAME PROJECTION TEST A	uto Igr	to Ignition Temperature Flammability Limits in Air by % in Volume:					
(aerosols) 12-16 Inch Flame Extension		N/E % LEL: N/E % UEL: N/E					
FLASH POINT AND METHOD USED (non-aerosols): N/A EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water fog.							
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.							
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.							
SECTION 4 - REACTIVITY HAZARD DATA							
STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR							
Incompatibility (Mat. to avoid): Strong oxidizers. Conditions to Avoid: Open flame, welding arcs, heat, sparks.							
Hazardous Decomposition Products: CO, CO2.							
SECTION 5 - HEALTH HAZARD DATA							
PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION [X]SKIN ABSORPTION []EYE []NOT HAZARDOUS							
ACUTE EFFECTS:							
Inhalation: Excessive inhalation of vapors can be harmful amd may cause headache, dizziness, asphyxia, anesthetic effects and possible							
unconsciousness.							
Eye Contact: Slight irritation. Skin Contact: Slight irritation.							
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea.							
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Petroleum distillate has caused kidney injury in							
laboratory animals. Stomach and intestine irritant.							
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.							
EMERGENCY FIRST AID PROCEDURES							
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.							
Skin Contact: Wash with soap and water. If irritated, seek medical attention.							
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.							
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.							
SECTION 6 - CONTROL AND PROTECTIVE MEASURES							
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor.							
Protective Gloves: Latex, if skin easily irritated.							
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV,							
Other Protective Clothing & Equipment: None							
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.							
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE							
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal							
regulations. DO NOT FLUSH TO SEWER.							
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.							
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.							
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove							
ignition sources.							
				74	A		

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only

THIS MSDS IS CURRENT AS OF March 18, 2001. The DATE PREPARED section is the original date assembled and remains current

THIS MSDS IS CURRENT AS OF March 18, 2001. The DATE PREPARED section is the original date assembled and remains current until a change is necessary. This is tracked internally at the manufacturer by these date codes and therefore must remain as the