

PRODUCT FACT SHEET

STREAMLIGHT <u>3N™ Propolymer</u> LED ALKALINE BATTERY-POWERED FLASHLIGHT

MARKET Industrial, Occupational Safety, Fire & Rescue, Sporting Goods, Law Enforcement,

APPLICATIONS: Security, Hardware/Tool, Consumer

DESCRIPTION: The 3N alkaline battery-powered flashlight features (3) three ultra bright white LEDs.

CASE MATERIAL: Impact resistant polymer body and face cap. Available in yellow and black.

DIMENSIONS: Length: 5.25 in. (13.33 cm) Diameter: Major Diameter: 0.96 in. (2.44 cm)

Body Diameter: 0.69 in. (1.75 cm)

WEIGHT: 2.1 oz (59.54 grams)*

LENS: Unbreakable polycarbonate lens with scratch resistant coating.

LIGHT SOURCE: 100,000 hour life LEDs.

LIGHT OUTPUT: 30 Lumens typical (3 white LEDs).

ON/OFF: Features momentary blink or constant "on" tail switch.

RUN TIME: Up to 120 hours continuous runtime.

BATTERY: Three "N" size alkaline batteries.

FEATURES: Features an integral pocket clip.

APPROVALS**: UL Classified for Class I, II, Division 1; Class III.

LISTED

UL Classified to Canadian safety standards for Class I, II, Division 1; Class III.

LISTED

Most models meet applicable European Community Directives, €, Including ATEX

Zone 0

WARRANTY: Limited lifetime warranty.

OPTIONAL

ACCESSORIES: Holster, Lanyard

*With batteries

** See product for specific ratings.

Assembled In The USA.

Document #110

Issued: 10/01/04 Revised: 02/05/07 Rev: 2

Page 1 of 1