

Stallion 12 SC

Self-Contained Carpet Extractor





Where productivity is the bottom line, the Stallion 12 SC cleans carpet quickly and efficiently. Top quality construction, remarkable ease of operation, and versatility combine for a machine that consistently outperforms the competition.

- The high-speed brush motor and brush guarantee powerful agitation to release deeply embedded soil and grit, extending carpet life.
- Large wheels, adjustable handle, and lightweight construction team up for easy handling and storage.
- A low-flow switch allows water conservation (about 38 percent less water is used) while keeping solution flow at the same great cleaning pressure.
- Four-wheel design for balance and reduced turning radius.
- Patented dual lift-off recovery buckets provide quick and convenient emptying.
- The brush system utilizes fully sealed stainless steel ball bearings for years of trouble-free operation.
- Maintenance is a breeze—just remove two screws and open up the clamshell design body for quick internal access.

NSS[®] Enterprises, Inc.

3115 Frenchmens Road Toledo, Ohio 43607-2958 USA www.nss.com



Printed on Green Seal[®] certified paper that contains 30% recycled post-consumer fiber.

Stallion 12 SC Specifications

	-	
Tanks		
Solution	12 gal (45.5 l) Dual 6 gal (45.5 l total)	
Recovery Solution Pump	100 PSI bypass	
Туре	Diaphragm type	
Watts	115 (110V) - 126.5 (230V)	
Vacuum Motors		
Туре	Dual, 2-stage tangential	
Voltage	110-120V, 220-240V available	
HP	3.5 HP (2.7 kilowatts)	
CFM	200	
Water Lift	76-in	
Current	120V - 15 amps, 240V - 8 amps	
Brush Motor		
Туре	Permanent magnet	
Voltage	110V - 120V or 220V - 240V	
HP	0.167 HP	
RPM	2,100	
Construction	Data sect a shuthulan s	
Tanks	Rotocast polyethylene	
Frame	Painted steel	
Wheels	Four 8-in (20 cm) non-marking grey tread 2 Brass	
Spray Jets Vacuum Shoe		
Brush	18-in (46 cm) corrosive-resistant cast aluminum	
Туре	15.25 (39 cm) nylon bristle, Chevron design	
RPM	2,100	
Bearings	Sealed; stainless steel	
Sound Level	77 dBA	
Cord		
Size	12-3 SJTW safety yellow with molded plug	
Length	50 ft (15 m)	
Accessory Valve	Quick-connect attachment; automatic valve actuated	
Dimensions		
Height	38 in (96.5)	
Length	48 in (122 cm)	
Width	19 in (48 cm)	
Weight		
Machine	120 lbs (54.5 kg)	
Shipping	136 lbs (62 kg)	
Shipping Class	125	
Warranty	3 year limited, 10 year poly parts	
Productivity	1,926 sq ft per hour (179 sq m per hour)
	NSS Enterprises, Inc. 3115 Frenchmens Road Toledo, OH 43607-2958	DISTRIBUT



- The clearview recovery tank top allows the 0 operator to easily see when the tanks need to be emptied.
- Patented dual lift-off recovery buckets P provide quick and convenient emptying.
 - The vacuum shoe covers an 18-in wide path.
- Two brass spray jets provide a powerful 4 blast of cleaning solution over the full width of the cleaning head.
- **5** Dual transport wheels allow easy transport and easy forward movement before each pull-back cleaning pass.
- A low-flow solution switch on the Stallion 6 12 SC allows the operator to use less water at the same PSI, conserving water without sacrificing cleaning power.
- The heavy-duty 12 ga cord, in safety yellow, Ø provides trouble-free service, and a 50-ft reach.

8 Convenient fingertip controls make it easy to activate the pump, vacuum motor, and brush.



The low-flow solution switch allows about 38% less water to be used, conserving a valuable natural resource.

The ergonomic handle and wheel carriage help prevent back strain when pushing machine forward before each pull-back cleaning stroke.

The dual recovery tanks are easy to empty into any toilet or sink, eliminating potentially harmful bending.



Toledo, OH 43607-2958 USA

P: (800) 677-1663 F: (419) 531-3761

mailus@nss.com

www.nss.com

UTED BY

Specifications subject to change without notice.