



For a durable, powerful floor machine in an economical package, choose the Mustang. Precision-balanced for easy operation and maneuverability, this machine scrubs, strips, spray buffs, polishes, and shampoos.

- The Mustang features a straight line planetary gear system that provides efficient transfer of power from the motor to the pad driver. This design ensures years of trouble-free operation.
- A mechanical lock-out on the handle must be released before the switch lever on the Mustang will activate. This special safety mechanism helps prevent unauthorized operation when the machine is unattended.
- The Mustang is ideal for schools, office buildings, and other facilities where appearances need to be kept up while holding equipment costs down.
- The Mustang comes with either a 1 HP or 1.5 HP 66-frame motor, and is available in 17- and 20-inch widths.

NSS Enterprises, Inc. 3115 Frenchmens Road Toledo, Ohio 43607-2958 USA www.nss.com



Mustang Specifications

5 .	
Pad Size	17 in (43 cm) or 20 in (51 cm)
Motor	
HP	1 HP or 1.5 HP
Speed	1700 RPM (1425 RPM for 240V)
Туре	66 frame, dual capacitor
Voltage	110-120V, 220-240V available
Current	
1 HP	12.6 amps @ 120V, 6.8 amps @ 240V
1.5 HP	15 amps @ 120V, 8.3 amps @240V
Gearbox	
1 HP	2-idler planetary with 11:1 ratio
1.5 HP	3-idler planetary with 11:1 ratio
Cord	Safety yellow
120V	50 ft (15.2 m) 14-3 ST
240V	75 ft (23 m) 16-3 ST
Sound Level	57.5 dBA

93 lbs (42.2 kg)

107 lbs (48.6 kg)

110 lbs (45.4 kg)

114 lbs (51.8 kg)

Weight (Shipping)

Weight (Machine)

17 in 1 HP

20 in 1 HP

17 in 1.5 HP

20 in 1.5 HP

112 lbs (50.8 kg)
126 lbs (57.2 kg)
119 lbs (54 kg)
133 lbs (60.4 kg)

Shipping Class 125

Productivity (17 in)

Polish	2,000 sq ft per hour (186 sq m)
Scrub	1,923 sq ft per hour (179 sq m)
Shampoo	1,000 sq ft per hour (93 sq m)
Spray Buff	1,724 sq ft per hour (160 sq m)

Productivity (20 in)

Polish	2,381 sq ft per hour (221 sq m)
Scrub	2,222 sq ft per hour (206 sq m)
Shampoo	1,033 sq ft per hour (96 sq m)
Spray Buff	2,000 sq ft per hour (186 sq m)



The Mustang features a mechanical lock-out on the handle, which must be released before the switch lever can be activated.

NSS Enterprises, Inc.

3115 Frenchmens Road Toledo, OH 43607-2958

P: (800) 677-1663 F: (419) 531-3761

mailus@nss.com www.nss.com Specifications subject to change without notice.



- Metal cord strain relief and internal compression lock prevent the cord from being pulled out of the machine.
- 2 Sturdy 1.5-in tube handle is chrome-plated to resist corrosion.
- **3** 360° non-marking bumper protects walls and fixtures from accidental damage.
- 4 5-in rear transport wheels make the Mustang easy to move to the job site.
- 5 Dual switch levers allow the operator to easily control the side-to-side movement of the machine.



The adjustable handle height allows ergonomic operation.

The rear wheels allow easy transport of the floor machine on stairs, and into and out of vehicles.

Precision-balanced for easy operation and maneuverability, this machine reduces the operator fatigue associated with most competitive swing machines.



Printed in USA

©2008 NSS Enterprises, Inc.

#9095901 REVE 11/08