S-20 20" AUTO SCRUBBER

TIER 1 SPECS. AFFORDABLE PRICE.

This machine may very well be the best value in auto scrubbers. The machine features specifications and attributes you would find in the premium price ranges, but at a mid-market price. Pacific Floorcare™ is a truly U.S. based, privately-owned company uniquely positioned to bring together this offering.

Training graphics are on the control panel. New or experienced operators learn as easy as 1, 2, 3!

- Clean on your schedule B with sound levels down to 63 dBA
 - Transport the machine without worry with frame and tank tie down points
 - Perform chemical-free finish removal with heavy-duty orbital head & 100 lb down pressure
 - Don't kneel or strain your back again with automatic on/off brush system



APPLICATIONS:

The S-20, available as pad assist or traction drive, rotary disk or rectangle, high-rpm orbital-motion head, is Purpose Built[™] for:

- Daily scrubbing & project work (deep scrub or strip jobs) of smaller facilities
- Dedicated facility or multi-facility route cleaning programs
- Small rooms, detail & edge cleaning in larger facilities
- Chemical-free finish removal! (orbital)
- Grout and porous floor scrubbing
- Entry-ways & lobbies
- Check-out aisles
- Spill clean-up & water recovery



pacific floor care.com

FEATURES

SPECIFICATIONS

| FEATURES | SPECIFICATI | UNS | |
|---|--|---|---|
| MODEL: | S-20 (Disk) Pad Assist | S-20 (Disk) Traction | S-20 (Orbital) |
| PART NUMBER(S): | 855401 w/wet batt & on-board chgr. 855402 w/MF batt & on-board chgr. 855407 w/wet batt & off-board chgr. 855408 w/MF batt & off-board chgr. | 855403 w/wet batt & on-board chgr. 855404 w/MF batt & on-board chgr 855409 w/wet batt & off-board chgr. 855410 w/MF batt & off-board chgr | 855405 w/wet batt & on-board chgr. 855406 w/MF batt & on-board chgr. 855411 w/wet batt & off-board chgr. 855412 w/MF batt & off-board chgr. |
| SOLUTION DELIVERY SYSTEM | | | |
| Solution capacity: | 11 gal | 11 gal | 11 gal |
| Solution control: | 05 gpm, variable, knob adjustment | 05 gpm, variable, knob adjustment | 05 gpm, variable, knob adjustment |
| SCRUBBING SYSTEM | | | |
| Cleaning path: | 20 in | 20 in | 20 in |
| Pad/brush size: | (1) 20 in | (1) 20 in | (1) 20 x 14 in |
| Productivity (per hour)-Theoretical max: | 23,800 ft ² | 23,800 ft ² | 23,800 ft ² |
| Productivity (per hour)-Average coverage rate*: | 10,630 ft ² | 14,175 ft ² | 14,175 ft² (scrubbing) 9,000 ft² (finish removal) |
| BRUSH DRIVE SYSTEM | | | |
| Brush motor horsepower: | .75 hp | .75 hp | 1.0 hp |
| Brush rpm: | 230 rpm | 230 rpm | 2,200 rpm |
| Brush/pad pressure: | 60 & 90 lb | 60 & 90 lb | 75 & 100 lb |
| Brush/pad attachment/removal: | Auto on/off | Auto on/off | Manual |
| RECOVERY SYSTEM | 1 | | |
| Recovery tank accessibility: | Full clean out access | Full clean out access | Full clean out access |
| Recovery tank capacity: | 13 gal (2 gal demisting chamber) | 13 gal (2 gal demisting chamber) | 13 gal (2 gal demisting chamber) |
| Vacuum motor: | .51 hp, 2-stage | .51 hp, 2-stage | .51 hp, 2-stage |
| Vac motor cfm: | 68 cfm | 68 cfm | 68 cfm |
| Squeegee width: | 30 in | 30 in | 30 in |
| DRIVE SYSTEM | | | |
| Drive type: | Pad assist | Traction | Traction |
| Motor horsepower: | NA | .25 hp | .25 hp |
| BATTERY SYSTEM | | | |
| System voltage: | 24 V | 24 V | 24 V |
| Battery amp hour rating: | 130 AH (wet) / 105 AH (MF) | 155 AH (wet) / 140 AH (MF) | 155 AH (wet) / 140 AH (MF) |
| Battery run time: | Up to 3 hours | Up to 3.5 hours | Up to 4 hours |
| Charger description: | On-board (standard) Off-board (optional) | On-board (standard) Off-board (optional) | On-board (standard) Off-board (optional) |
| MACHINE SPECIFICATIONS | | | |
| Product length: | 50 in | 50 in | 45 in |
| Product width (without squeegee): | 21 in | 21 in | 21 in |
| Product height: | 43 in | 43 in | 43 in |
| Product weight (with batteries): | 380 lb | 380 lb | 410 lb |
| Sound level (operator's ear): | 63 dBA | 63 dBA | 65 dBA |
| Construction: | Rotationally molded polyethylene tanks, powder coated steel frame | Rotationally molded polyethylene tanks, powder coated steel frame | Rotationally molded polyethylene tanks, pow- der coated steel frame |
| WARRANTY | | | |
| Rotationally-molded tanks: | 10 years | 10 years | 10 years |
| Parts (excluding wear items): | 3 years | 3 years | 3 years |
| Isolators: | N/A | N/A | 2 years or 1,200 hours |
| Labor: | 1 year | 1 year | 1 year |
| OPTIONAL ACCESSORIES | | | |
| Available accessories: | Brushes 850901 scrub-poly 850902 scrub-nylon 850903 scrub-grit Pad Driver 855901 855008 Parking Brake | Pads-Case of 5, 20 in 475950 black, stripping 475951 blue, scrubbing 973011 red, buffing & cleaning 475960 white, buffing Squeegee Blades, Urethane 850703 front 850704 rear | Pads-Case of 10, 20 x 14 in 855902 maroon, surface prep 855908 black, stripping 855906 purple, diamond clean/polish 855904 red, buffing & cleaning 855007 HydroLink® Battery Watering Sys- tem (applicable to 155AH battery packs only) |
| | _ | | |
| *Productivity calculations utilize key factors from the I | 855009 Digital Hour Meter** | | |

*Productivity calculations utilize key factors from the ISSA 540 cleaning times handbook **Optional on disk units & standard on orbital units Note: Specifications subject to change without notice



GENUINE SERVICE PARTS PURPOSE BUILTTM TO PROVIDE MAX PERFORMANCE

Why buy a copy when you can get the original parts – the ones actually used in the machine's original design work the best. Not only do you get maximum performance, but you also reduce hassle and downtime. Be sure to contact Pacific Floorcare or a local authorized distributor when you need authentic service parts.



pacificfloorcare.com (800) 968-1332