UL Rated 3-A, 40-B:C



Description

Suitable for use on Class A (trash, wood & paper), Class B (liquids & gases) and Class C fires (energized electrical equipment).

The PRO 340 is fitted with a pressure gauge that provides at-a-glance status, is manufactured from lightweight aluminum cylinder with a tough aluminum valve assembly.

Features bilingual nameplate and carton.

FOR MODERATE HAZARDS

Features

- Multipurpose Fire Extinguisher
- Aluminum cylinder
- Tough aluminum valve assembly
- Pressure gauge allows for immediate pressure status check
- Rechargeable unit.
- Assembled in Mexico from global components
- 6 year warranty
 - UL rated 3-A:40-B:C
- UL approved wall hanger Coast Guard (U.S.C.G)
- approved when fitted with optional mounting bracket
- Powder coated cylinder for corrosion protection
- Optional metal strap bracket Pt # 466400



Pt # 21005782 - 4 pack UPC: 0-47871-05782-5 I2F - 10047871057822

For use on the following types of fire:









A 3-A:40-B:C rated extinguisher is required

for protecting MODERATE hazard occupancies such as: home garage & workshop, light manufacturing, dining areas, auto showrooms, parking garages & storage areas.

roduct Specification

Product Specification				
Net agent weight (Average)	5.5 lb.			
Unit weight (Average)	9.0 lb.			
Diameter	4.5 inches			
Height	16.5 inches			
Discharge time	13-15 seconds			
Discharge range	10-15 feet			
Operating pressure	195 psi			
Cylinder	Seamless aluminum			
Valve/handle/lever Aluminum				
Strap Bracket (not supplied)	U.S.C.G approved			

Packaging Options



Packaging dimensions (inches)

_				
		Depth	Width	Height
	Carton	4.75	6.0	17.0
	Master Pack	13.0	17.25	9.87