



Product Technical Sheet

SSS CHEWING GUM REMOVER

Description: This gum removing product should be used on tables, chairs, floors and other nonporous surfaces to remove chewing gum. A refrigerant freezes the gum which releases the adhesions between the gum and surface.

Directions: Insert the extension tube into the valve tip. Direct the tube at the point of adhesion between the gum and surface. When the tube is within 1" of the gum, spray until frost appears. In most cases the gum will fall off by itself. In stubborn dried on cases, slight prodding with a screwdriver or putty knife may be needed. Leaves no mark or stain on the surface.

Health Hazard Data: Extremely flammable. Contains isobutane/propane blend. Use only in well ventilated area. Do not use near heat, sparks, open flame or other sources of ignition. Avoid contact with skin or eyes. Contents in contact with skin can cause frostbite. If blistering occurs, see physician immediately. Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. KEEP OUT OF REACH OF CHILDREN.

Spill Or Leakage Procedures: Remove ignition sources. Ventilate area to disperse vapors. Do not flush to sewer. Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.

Product Specifications:

Wt./12oz. can:	6 Ounces
USDA Category:	N/A
Classification:	Aerosol Chewing Gum Remover
General Appearance:	Frigid Liquid Which Quickly Becomes Gas
Color:	Colorless
Odor:	Odorless
pH:	N/A
Vapor Pressure At 70°F:	70 psig
Spray Pattern:	Blasting Mist
Flammability:	Extremely Flammable per CPSC Flame Projection Test
NFPA Code 30B:	Level 3